


Technical sheet

MHT 1490

Telehandlers




Capacities	Metric
Max. capacity	9000 kg
Max. lift height	14 m
Max. reach	9.55 m
Weight and dimensions	
l2 - Overall length of fork carriage	6.70 m
b1 - Overall width	2.50 m
h17 - Overall height	3 m
y - Wheelbase	3.37 m
m4 - Ground clearance	0.44 m
b4 - Overall cab width	0.93 m
a4 - Tilt-up angle	18 °
a5 - Tilt-down angle	117 °
Wa1 - Frame outer turning radius	4.01 m
Unladen weight (with forks)	20800 kg
Standard forks	48 x 8 x 2
Performances	
Lifting	14.90 s
Lowering	12.80 s
Telescope extension	18.90 s
Retracting the telescope	10.80 s
Scoop	6.60 s
Dump	5.30 s
Engine	
Brand	Mercedes
Environmental standards	Stage IV / Tier 4 Final
Model	OM934LA
Number of cylinders - Capacity	4 - 5100 cm³
Power	176 hp / 129 kW
Max. torque	750 Nm at 1600 rpm
Laden drawbar pull	10900 daN
Transmission	
Type	Hydrostatic
Number of gears (forward/reverse)	2/2
Max. speed of travel (may vary according to the applicable regulation)	31 km/h
Parking brake	Automatic negative parking brake
Service brake	Hydraulic
Hydraulics	
Type of pump	Variable Flow
Hydraulic flow rate - Pressure	180 l/min - 300 bar
Tank capacities	
Engine oil	21 l
Hydraulic oil	275 l
Fuel	315 l
AdBlue® Diesel Exhaust Fluid (DEF)	63 l
Noise & vibration	
Noise at driving position (LpA)	82 dB(A)
Noise to environment (LwA)	106 dB(A)
Vibration on hands/arms	<2.5 m/s²
Miscellaneous	
Steering wheels / Driving wheels	4 / 4
Safety	Standard EN 15000 Cab ROPS - FOPS Level 2
Controls	JSM





Load chart


Machine on tyres with forks - CoG 600 mm



Rotation on lowered stabilisers with forks - CoG 600 mm







Siège Social
430 rue de l'Aubinière - 44150 Ancenis Cedex - France
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508 RCS Nantes