











**CVS Ferrari F500 - RS7**

|   |      |                           |
|---|------|---------------------------|
| Attachment type                                     |      | 20'/40' Top Pick Spreader |
| Load capacity on tires at 1st/2nd/3rd row (no stab) | kg   | 46.000   44.000   25.000  |
| Load centre distance at 1st/2nd/3rd row             | mm   | 1.780   3.850   6.400     |
| Load capacity on stabilizers at 1st/2nd/3rd row *   | kg   | 46.000   46.000   33.000  |
| Load centre to front face of the truck              | mm   | 930                       |
| Lifting height under twist-lock                     | mm   | 16.200                    |
| Stacking Ability – containers                       |      | 1 over 5 = 6 x 8'6"       |
| Wheelbase   | mm   | 7.500                     |
| Service weight – unladen                            | kg   | 84.000                    |
| EU Stage 3a Engine make&model (Rated Power)         | (kW) | CUMMINS QSM11 (250)       |
| EU Stage 4 Engine make&model (Rated Power)          | (kW) | SCANIA DC13 (257)         |
| Transmission make&model                             |      | DANA TE32                 |
| Service Brakes                                      |      | Wet Disk on front wheels  |
| Tires size  |      | 18.00-33                  |
| Overall width – excluding Spreader                  | mm   | 4.185                     |
| Overall length – including spreader                 | mm   | 12.000                    |
| Overall height                                      | mm   | 4.800                     |
| Seat height   | mm   | 2.820                     |
| Spreader rotation – clockwise/anticlockwise         | deg  | -0,538461538              |
| Spreader side-shift – left / right                  | mm   | -1                        |
| Boom Angle (min / max)                              | deg  | 0 /60                     |

\* optional



**CVS Ferrari F500 - RS8**

|   |            |                           |
|---|------------|---------------------------|
| Attachment type                                     |            | 20'/40' Top Pick Spreader |
| Load capacity on tires at 1st/2nd/3rd row (no stab) | kg         | 46.000   46.000   28.000  |
| Load centre distance at 1st/2nd/3rd row             | mm         | 1.780   3.850   6.400     |
| Load capacity on stabilizers at 1st/2nd/3rd row *   | kg         | 46.000   46.000   38.000  |
| Load centre to front face of the truck              | mm         | 930                       |
| Lifting height under twist-lock                     | mm         | 16.200                    |
| Stacking Ability – containers                       |            | 1 over 5 = 6 x 8'6"       |
| Wheelbase   | mm         | 8.000                     |
| Service weight – unladen                            | kg         | 87.000                    |
| EU Stage 3a Engine make&model (Rated Power)         | (kW)       | CUMMINS QSM11 (250)       |
| EU Stage 4 Engine make&model (Rated Power)          | (kW)       | SCANIA DC13 (257)         |
| Transmission make&model                             |            | DANA TE32                 |
| Service Brakes                                      |            | Wet Disk on front wheels  |
| Tires size  |            | 18.00-33                  |
| Overall width – excluding Spreader                  | mm         | 4.185                     |
| Overall length – including spreader                 | mm         | 12.000                    |
| Overall height                                      | mm         | 4.800                     |
| Seat height   | mm         | 2.820                     |
| Spreader rotation – clockwise/anticlockwise         | deg        | -0,538461538              |
| Spreader side-shift – left / right                  | mm         | -1                        |
| <b>Boom Angle (min / max)</b>                       | <b>deg</b> | <b>0 /60</b>              |

\* optional

